

HDP60-XXXYYT

65 Watt Switch Mode Desktop Power Supply



Features

- High reliability
- Built-in OVP, OCP, and SCP
- 100% smart burn-in test for 4 hours

Dimensions

120 x 52.5 x 32.3 mm

Weight

260g



Electrical Specifications

| | |
|---------------------|--|
| INPUT RANGE | 100 - 240 VAC (Full Range), 50/60 Hz |
| INPUT CURRENT (RMS) | 1.5A@90VAC; 0.75A@264VAC max |
| VOLTAGE RANGE | DC 8 - 30V output |
| VOLTAGE REGULATION | ±5% @ constant voltage mode |
| CURRENT RANGE | 0.1 - 5.0A |
| MAX OUTPUT POWER | 65W Max |
| PROTECTION | Over Current, Over Voltage, Short Circuit Protection |
| EFFICIENCY | Meets CEC VI |

Environmental & Reliability

| | |
|-----------------------|---|
| OPERATING TEMPERATURE | 0°C ~ +45°C ambient |
| STORAGE TEMPERATURE | -20°C ~ +80°C |
| OPERATING HUMIDITY | 10% ~ 90% Non-Condensing |
| RELATIVE HUMIDITY | 5% ~ 95% Non-Condensing |
| MTBF | >25k Hours at 80% load and 25°C ambient temperature |

Safety, Efficiency, & EMC Standards

CB, UL, ETL, FCC, GS, CE, LVD, SAA, RCM, C-Tick, CCC, PSE, BIM, EAC, Argentina S-Mark, RoHS, REACH, PAHS

